# Boston Properties The Link

Exterior and Wayfinding Signage
Design Development
3.19.19
Bulletin 2



## Signage Typography

## **ABCDEFGHIJKLMNOPQRSTUVWXYZ** abcdefghijklmnopqrstuvwxyz 1234567890

T1- Gotham Medium

## **ABCDEFGHIJKLMNOPQRSTUVWXYZ** abcdefghijklmnopqrstuvwxyz 1234567890

T2- Avenir Next Bold

## Signage Logos



## **Sinage Project Materials**



Dark Teal



Light Teal



Р3 Brushed Aluminum



Р4 White





Light Magenta



P6

Dark Magenta



V1 Magenta



Translucent White Vinyl






Acrylic

Α1





3M 7725-020 Matte White Vinyl



Frosted Acrylic

Boston **Properties** 

The Link

## Leverage/

Leverage Design Group, Inc. © 2019


No portion of this drawing may be reproduced without written consent of Leverage Design Group, and related sheets are for design intent only.

Leverage Design Group, Inc. does not represent that the design of the elements on the sheets are able to Design Group, Inc. in the event of concern or disagreement with the contractibility and design

REV # DESCRIPTION BY DA	TE
<u>^</u> 1\	
<u>/2</u>	
<u></u>	
<u></u>	
<u>/</u> 5\	
<u>6</u>	
Δ	
<u> </u>	

## **Project Standards**





## Boston Properties

The Link

## Leverage/


Leverage Design Group, Inc. © 2019

No portion of this drawing may be reproduced without written consent of Leverage Design Group, Inc. The design elements represented on this sheet and related sheets are for design intent only.

Leverage Design Group, Inc. does not represent that the design of the elements on the sheets are able to be fabricated entirely as shown. Contractor/fabricator to review documents for contractibility, performance and structural soundness and to notify Leverage Design Group, Inc. in the event of concern or disagreement with the contractibility and design intent of the elements as depicted on the sheets.

REV #	DESCRIPTION	BY	DATE
<u>^</u> 1 _			
<u>^2</u> _			
<u> </u>			
<u>4</u> _			
<u></u>			
<u></u>			
<u>^</u>			

# **B1**Exterior Vinyl Signage



Boston Properties

The Link

## Leverage/


Leverage Design Group, Inc. © 2019

No portion of this drawing may be reproduced without written consent of Leverage Design Group, Inc. The design elements represented on this sheet and related sheets are for design intent only.


Leverage Design Group, Inc. does not represent that the design of the elements on the sheets are able to be fabricated entirely as shown. Contractor/fabricator to review documents for contractibility, performance and structural soundness and to notify Leverage Design Group, Inc. in the event of concern or disagreement with the contractibility and design intent of the elements as depicted on the sheets.

REV#	DESCRIPTION	BY	DATE	
<u>^</u> 1				
2				
<u>3</u>				
4				
<u>/</u> 5				
<u></u>				
<u></u>				

**B2**Lobby Signage




1/4" THICK FROSTED ACRYLIC PANEL W/ SURFACE APPLIED LOGO; STOOD-OFF FROM WALL USING EXISTING HARDWARE; FINAL DIMENSIONS TO BE VERIFIED






1/4" THICK BRUSHED ALUMINUM PANEL W/ 1/4" THICK PAINTED ACRYLIC LOGO; PANEL STOOD-OFF FROM WALL USING EXISTING HARDWARE; FINAL DIMENSIONS TO BE VERIFIED





1/4" THICK PAINTED METAL PANEL W/ ETCHED AND INFILLED TEXT PAINTED PANEL RETURNS; PANEL STOOD-OFF FROM WALL HARDWARE NOT ON PANEL FACE; FINAL DIMENSIONS TO BE VERIFIED





Context Elevation
scale: NTS

Boston Properties

The Link

## Leverage/

Leverage Design Group, Inc. © 2019


No portion of this drawing may be reproduced without written consent of Leverage Design Group, Inc. The design elements represented on this shee and related sheets are for design intent only.

Leverage Design Group, Inc. does not represent that the design of the elements on the sheets are able to be fabricated entirely as shown. Contractor/fabricator to review documents for contractibility, performance and structural soundness and to notify Leverage Design Group, Inc. in the event of concern or disagreement with the contractibility and design intent of the elements as depicted on the sheets.

REV #	DESCRIPTION	BY	DATE
<u>^</u> 1 _			
<u>^2</u> _			
<u>3</u> _			
4 _			
5 _			
<u>6</u> _			
<u> </u>			

**B5**Elevator Signage





A-FRAME SANDWICH BOARD (STOCK BOUGHT) TOP FRAME TO HOLD BRAND LOGO AND NAMING BOTTOM FRAME TO HOLD CHANGEABLE CONTENT

1 Elevation scale: 1" = 1'-0"

## Boston Properties

The Link

## Leverage/

Leverage Design Group, Inc. © 2019

No portion of this drawing may be reproduced without written consent of Leverage Design Group, Inc. The design elements represented on this sheet and related sheets are for design intent only.

Leverage Design Group, Inc. does not represent that the design of the elements on the sheets are able to be fabricated entirely as shown. Contractor/fabricator to review documents for contractibility, performance and structural soundness and to notify Leverage Design Group, Inc. in the event of concern or disagreement with the contractibility and design intent of the elements as depicted on the sheets.

REV #	DESCRIPTION	ВУ	DATE
<u>^î</u> _			
<u>^2</u>			
<u></u>			
<u>4</u>			
<u></u>			
<u>^6</u>			
<u> </u>			

# **B6**Outdoor Portable Signage

## Digital Frames:

## Option 1:

- -Can be battery powered and is built for indoor/outdoor environments.
- -One Sided messaging
- -Can have touchscreen abilities
- -Does not have a heavy base and could blow over in high winds
- -Price not listed. Need to contact vendor for cost

Link: http://www.metroclick.com/digital-sandwich-board/

## Option 2:

- -Has small HD Screen for changeable messages
- -Needs a plug for power
- -Mostly consists of grease board and not digital screen (back is grease board)
- -Price not listed. Need to contact vendor for cost

Link: <a href="https://www.pacificdigitalsigns.com/products/digital-sandwich-board/sandwichboard/">https://www.pacificdigitalsigns.com/products/digital-sandwich-board/sandwichboard/</a>

## Option 3:

- -One sided sign
- -Needs to be plugged in
- -Have seen a video of it being outdoors, so I assume it's outdoor friendly
- -Does not have a heavy base and could blow over in high winds
- -Price not listed. Need to contact vendor for cost

Link: <a href="https://www.pacificdigitalsigns.com/products/digital-sandwich-board/">https://www.pacificdigitalsigns.com/products/digital-sandwich-board/</a>







## Boston Properties

The Link

## Leverage/

Leverage Design Group, Inc. © 2019

No portion of this drawing may be reproduced without written consent of Leverage Design Group, Inc. The design elements represented on this sheet and related sheets are for design intent only.

Leverage Design Group, Inc. does not represent that the design of the elements on the sheets are able to be fabricated entirely as shown. Contractor/fabricate to review documents for contractibility, performance and structural soundness and to notify Leverage Design Group, Inc. in the event of concern or disagreement with the contractibility and design intent of the elements as depicted on the sheets.

REV#	DESCRIPTION	ВҮ	DATE	
1				
2				
<u>3</u>				
4				
<u> </u>				
<u></u> 6				
<u> </u>				

#### **B6**

Outdoor Portable Signage

## Static Frames:

## Option 1:

- -Will do well in the wind
- -Fits a 24" x 36" image (double sided)
- -28 pounds, might be difficult to transport
- -Cost \$227

Link: https://www.allposterframes.com/P-31889/Spring-Base-Outdoor-Snap-

Frame-24x36-Anti-Glare-Lenses-Protect-Graphics?st=Category&sid=29056



- -Weighted base for wind resistance
- -has 2 wheels for transportation
- -Fits a 24" x 36" image (double sided)
- -Cost \$190.99

Link: <a href="https://www.sidewalksigns2go.com/P-21368/Outdoor-Free-Standing-Signs-Non-Glare-">https://www.sidewalksigns2go.com/P-21368/Outdoor-Free-Standing-Signs-Non-Glare-</a>

**PVC-Lens?st=Category&sid=29272** 

## Option 3:

- -15 pounds, so can be carried
- -Fits a 22" x 28" image (double sided)
- -Has 8.5" x 22" header that can hold a permanent Link logo or brand element
- -May blow over in high winds
- -Cost \$130.99

Link: <a href="https://www.displays2go.com/P-6931/Sidewalk-Signs-with-22-x-28-Snap-Frame-with-Header-Area?st=Category&sid=3952">https://www.displays2go.com/P-6931/Sidewalk-Signs-with-22-x-28-Snap-Frame-with-Header-Area?st=Category&sid=3952</a>







## Boston Properties

The Link

## Leverage/

Leverage Design Group, Inc. © 2019

lo portion of this drawing may be reproduced vithout written consent of Leverage Design Group, nc. The design elements represented on this shee nd related sheets are for design intent only.

Leverage Design Group, Inc. does not represent the the design of the elements on the sheets are able to be fabricated entirely as shown. Contractor/fabricator review documents for contractibility, performanc and structural soundness and to notify Leverage Design Group, Inc. in the event of concern or disagreement with the contractibility and design intent of the elements as depicted on the sheets.

REV#	DESCRIPTION	BY	DATE	
<u></u>				
<u>^2</u> _				
<u> </u>				
<u>4</u> _				
<u>_</u>				
<u></u>				
<u>^</u>				

## **B6**

Outdoor Portable Signage

#### 1.0 DESIGNER'S RESPONSIBILITIES

#### A Review & Approval

- 1. Attention is directed to the fact that Designer review is only to check for general conformance with the design concept of the project and general compliance with Design Documents. No responsibility is assumed by Designer for correctness of dimensions, details, quantities, procedures shown on shop drawings, or submittals.
- 2. It shall be the responsibility of the Designer to review all fabricator submittals with reasonable promptness on basis of design concept of project and information contained in Design Documents.
- 3. Omission in shop drawings of materials indicated in Design Documents mentioned in Specifications, or required for proper execution and completion of work, does not relieve the Fabricator from responsibility for providing such materials. Fabricator is responsible for accuracy, dimensions, quantities, strength of connection, coordination with various trades, and conformance to project requirements.
- 4. Approval of a separate or specified item does not necessarily constitute approval of an assembly in which the item is a part of.
- 5. It shall be the responsibility of the Designer to review to affix stamp and initials or signature acknowledging review of submittal as follows: As Noted, Revise & Resubmit, Rejected, For Info Only

#### **B** Artwork

- 1. Designer to provide artwork digitally via Adobe Illustrator
- 2. O FABRICATOR'S RESPONSIBILITIES

#### A General

- 1. It shall be the responsibility of the Fabricator that all finished work be of the highest quality to pass eye-level examination and scrutiny by the Client and Designer.
- 2. It shall be the responsibility of the Fabricator to fabricate and install all sign types, messages and graphics as indicated in the Design Documents.
- 3. It shall be the responsibility of the Fabricator to assist and collaborate with all Clients teams, agencies, sub-contractors (as needed) and Designer to complete project scope.
- 4. It shall be the responsibility of the Fabricator to provide, manage and maintain project fabrication and installation schedules and to provide updates to these schedules as needed to Client and Designer.
- 5. It shall be the responsibility of the fabricator to provide timely notice to Client and Designer for submittals of information, drawings and other details needed to meet fabrication and installation schedule.

#### **B Structural Design**

1. Details on Drawings indicate a design approach for sign fabrication but do not necessarily include all fabricating details required for the complete structural integrity of the signs, including consideration for static, dynamic, and erection loads during handling, erecting, and service at the installed locations, nor do they necessarily consider the preferred shop practices of the individual sign fabricators. Therefore, it shall be the responsibility of the Fabricator to perform the complete structural design of the signs and to incorporate all the reasonable

safety factors necessary to protect the Client, its representatives, and Designer against public liability.

2. Designs which survive rational engineering analysis will be acceptable, provided that shop drawings, including structural design, are approved by the Client and Designer.

#### C Code Compliance

1. It shall be the responsibility of the Fabricator to ensure that all signs meet all applicable local, state, and national codes, as well as testing laboratory listings where required.

#### **D** Samples

- 1. Allow 5 business days for the Client and Designer to review and process samples
- 2. The Fabricator shall submit physical samples of sufficient size and quantity to illustrate color, materials, finishes, equipment or workmanship, and to establish standards by which completed work will be judged. Samples must represent the functional characteristics of the product or material, with integrally related parts and attachment devices, colors, and finishes.
- 3. All samples to have a place for stamp approval.
- 4. Submit (2) complete sets of samples to Designer for review.
- 5. Submit (1) complete set of samples for Client review.
- 6. Submit full 6" x 6" set of all specified paint colors and finishes on specified materials.
- 7. Submit sample of each type of fastener to be used, as required.
- 8. Submit other items as may be required by Client and Designer, or as noted on the drawings or herein.

#### **E Prototypes**

1. Submit prototypes as may be required by Client and Designer, or as noted on the drawings or herein.

#### F Shop Drawings

- 1. Allow 5 business days for the Client and Designer to review and process shop drawings.
- 2. The drawings in this package are for design intent only. The Fabricator is responsible for the proper engineering of all items and verification on site of all installation requirements.
- 3. Provide shop drawings for all items in the Design Documents.
- 4. Provide (2) complete sets of shop drawings to Designer for review. Allow 5 business days for proper review of Shop Drawings by Designer.
- 5. Provide (1) complete set of shop drawings to Client for review.
- 6. Provide internal structure, dimensions, and specifications for all items in the Design Documents.
- 7. Provide all structural, stamped engineering drawings by licensed engineer in state where project will be installed.
- 8. Provide fabrication and installation drawings for each sign type. Indicate dimensions, materials, finishes, fastening, anchorage, joining, sealing, backing, utility requirements, rough-in, and adjacent related site conditions.

# Boston Properties

The Link

## Leverage/

Leverage Design Group, Inc. © 2019

No portion of this drawing may be reproduced without written consent of Leverage Design Group, Inc. The design elements represented on this sheet and related sheets are for design intent only.

Leverage Design Group, Inc. does not represent that the design of the elements on the sheets are able to be fabricated entirely as shown. Contractor/fabricator to review documents for contractibility, performance and structural soundness and to notify Leverage Design Group, Inc. in the event of concern or disagreement with the contractibility and design intent of the elements as depicted on the sheets.

REV #	DESCRIPTION	ВҮ	DATE
<u> </u>			
<u>^2</u> _			
<u>3</u> _			
<u> </u>			
<u> </u>			
<u>6</u> _			
<u> </u>			

# Performance Specifications

- 9. Submit, color production artwork of all sign messages in each typeface to demonstrate proper spacing (black text on white background, outline not accepted) prior to fabrication.
- 10. Indicate revisions date as required, and resubmit as specified for initial submittal.
- 11. Indicate on drawings all changes that are different than those requested by the Designer.
- 12. Submit new data and samples in accord with same criteria as required for first submittals.

#### **G Product Data**

- 1. Submit product data for sign systems, fixtures, material descriptions, components, standard profiles, and finishes.
- 2. Submit Color charts for finish indicating manufacturer's colors available for selection.
- 3. Include sample of warranty.

#### **H** Inspection

- 1. Client and Designer reserve the right to inspect work in the fabrication shop before it is shipped to the job site for installation.
- 2. Fabricator shall inspect installation locations for conditions which will adversely affect execution, permanence and quality of work, and shall not proceed with installation until unsatisfactory conditions have been corrected.
- 3. First article of production-run items, both large and small, will be reviewed by the Client and Designer before production run is commenced.

#### I Installation

- 1. Installation of all fabricated signs, including all fasteners and fastenings and related electrical connections; all foundations for all signs in Design Documents
- 2. Coordination with Client and Designer during all phases of development, fabrication, and installation.
- 3. Coordination with other trades, i.e., electrical contractors, etc.
- 4. Coordination and verification of all messages revisions with Client.
- 5. Verify the exact location with the Designer and Client for all signs which are not precisely dimensioned on the Drawings.
- 6. Except as may be specifically indicated otherwise on the drawings, install prefabricated work plumb, level, square, and true to line.
- 7. Securely anchor work in proper location using anchors, fasteners, or other methods approved on shop and erection drawings. All anchors/fasteners shall be appropriate for the anchorage condition.

#### J Fabrication

- 1. Construct all work to eliminate burrs, dents, cutting edges, and sharp corners.
- 2. Finish welds on exposed surfaces to be imperceptible in the finished work.
- 3. Except as indicated or directed otherwise, finish all surfaces smooth.

- 4. Surfaces which are intended to be flat shall be without dents, bulges, oil canning, gaps, or other physical deformities.
- 5. Surfaces which are intended to be curved shall be smoothly free-flowing to required shapes.
- 6. Except where approved otherwise by Designer, or specified in the Design Documents, conceal or counter-sink all fasteners.
- 7. Make access panels tight-fitting, lightproof, and flush with adjacent surfaces.
- 8. Conceal all identification labels and U.L. labels to conform to U.L. Codes.
- 9. Carefully follow manufacturer's recommended fabricating procedures regarding expansion/contraction, fastening, and restraining of acrylic plastic.
- 10. Exercise care to assure that painted, polished, and plated surfaces are unblemished in the finished work.
- 11. Isolate dissimilar materials. Exercise particular care to isolate nonferrous metals from ferrous metals.
- 12. All illumination shall be even and without hotspots.
- 13. Ease all exposed metal edges.

#### K Punch List

- 1. When Fabricator considers the work has reached final completion (that is, when less than one percent of the Contract remains to be completed), submit written notice, together with a written list of items to be completed or corrected.
- 2. The Client and Designer will inspect the status of completion and prepare a "Punch List" setting forth in detail any items on the Fabricator's list and additional items found unacceptable. When the Punch List is complete, the Client will arrange a meeting with the Fabricator to identify and explain all items and respond to questions regarding the work which must be done before final acceptance.
- 3. Fabricator shall correct Punch List items within a time frame established when the punch list is made. The time frame for completion of the Punch List items shall not exceed the completion date of the Contract. The Contract shall not be considered complete until Punch List items are completed.

#### 3.0 PRODUCTS

#### A Metal

- 1. Sheet Aluminum: Alloy 5000 Series for anodized finish; Alloy 3000 Series for painted finish.
- 2. Extruded Aluminum: ASTM B221M, alloy 6063-T5/T52.
- 3. Stainless Steel Pipe: ASTM A312/A312M, Grade TP304
- 4. Stainless Steel Pipe Sheets: ASTM A240. UNS Number S30200 or S30400.
- 5. Steel Tubing: ASTM A500 or A501
- 6. Steel Plates, Shapes and Bars: ASTM A36/A36M.
- 7. Structural Steel Sheet: Hot-rolled, ASTM A570/A570M, [Cold-rolled ASTM A611,] Class 1; of grade required for design loading.
- 8. Cold-Rolled Steel Sheet, Commercial Quality: ASTM A366/A366M.
- 9. Metal thickness indicated establishes minimum conditions.
- 10. When metal thickness is not indicated, provide thickness most appropriate for Project condition to prevent oil canning and warping, but not less than following:
  - a. Sheet steel [Galvanized]: 1 mm [(20 gage)] nominal thickness.

## Boston Properties

The Link

## Leverage/

Leverage Design Group, Inc. © 2019

No portion of this drawing may be reproduced without written consent of Leverage Design Group, Inc. The design elements represented on this sheet and related sheets are for design intent only.

Leverage Design Group, Inc. does not represent that the design of the elements on the sheets are able to be fabricated entirely as shown. Contractor/fabricator to review documents for contractibility, performance and structural soundness and to notify Leverage Design Group, Inc. in the event of concern or disagreement with the contractibility and design intent of the elements as depicted on the sheets.

REV#	DESCRIPTION	BY	DATE
<u>^</u> _			
<u>2</u> _			
4			
<u></u>			
<u> </u>			

# **Performance Specifications**

- b. Aluminum: 3.125 [2.25] mm [(0.125 [0.090] inch)] thickness minimum.
- c. Stainless Steel: 1 mm [(20 gage)] nominal thickness.
- d. Muntz Metal: Nominal 2.5 mm [(7.2 ounce)] thick.

#### **B** Plastic

- 1. Photopolymer: Exterior grade consisting of 1/32 inch thick exterior grade photopolymer layer of PVA/urethane base over integral layer of 1/8 inch thick phenolic base plate.2. Minimum 90 to 95 Shore 'D' Hardness.
- 3. Braille: Maximum surface diameter of 0.30 inch rounded.

#### C Acrylic

- 1. Material: Methylmethacrylate polymers.
- 2. Type: Solid sheet, laminated sheet, or cast acrylic in size, thickness, clarity, opacity, texture, and color required for Project.

#### D Silk Screening

- 1. Screen Material For Screen Printing Process: Stainless steel, nylon or polyester with 250 lines per inch, or finer
- 2. Use 16 XX screen for printing on cloth fabric.
- 3. Ink: Available in published color systems with full range of accent or pure spectrum colors, earth colors, and unlimited mixtures of colors.
- 4. Execute silk-screening from photoscreens, film positives, or developed negatives.
- 5. Execute silk-screen printing to ensure edges and corners of finished letter forms are true and clean. Letter forms with rounded positive or negative corners, edge buildup, or bleedings, voids, gaps, streaks, hot-spots, or other defects, will not be accepted.
- 6. Do not use inks which have been packaged over 6 months, except such products that are known to have long package stability when unopened and then only when guaranteed by the manufacturer. Inks shall be free from skins, lumps, and foreign matter. Oils, thinners, and driers delivered to the job shall be only those approved for use by the manufacturer.

#### E Adhesive Film

1. Computer Cut Vinyl Graphics: Pressure sensitive adhesive type; Thickness: 0.11 mm [(4.3 mils)]; Spacing: Computer default for font selected, unless otherwise shown or scheduled. Optically review and refine kerning pairs to adjust spacing of letters for visual consistency; Color: As shown or scheduled.

#### F Illumination

- 1. Code: Conform to National Electrical Code for electrical and communication components, materials, assemblies, and systems.
- 2. Lamps:
  - a. Type: Provide wattages and lamp type required by use conditions to provide uniform illumination with no hot spots or dim surfaces.
  - b. Neon: 5 mm [(3/16 inch)] to 25 mm [(1 inch)] glass tubing as determined by design.
  - c. Color: As selected by Designer
  - d. Transformers: Provide 60 MA transformers for neon units.
- 3. Ballasts: High power factor type as required by work conditions.

- 4. Disconnects:
  - a. Type: Enclosed, heavy duty, fused or unfused.
- 5. Locations: Provide NEMA 1 for dry locations and proper enclosure for others.
- 6. Conductors: THHN, No. 12.
- 7. Accessories: Provide supports, hangers, and other accessories as required

#### **G** Routing

- 1. Water jet. High pressure water jet adjustable for cut-outs and for engraving surfaces.
- 2. Machine routing.

#### H Fabrication Aluminum Cabinets And Pan-Formed Panels

- 1. Aluminum sign cabinets: Aluminum signs shall be fabricated from cold rolled pattern leveled sheet aluminum, conforming to ASTM B209, Alloy No. 5005H32. Each panel shall be shop formed in dies from a single sheet of material. Corners shall be coped, continuous heliarc welded, and ground smooth on exposed faces.
- 2. Illuminated messages shall be cut from aluminum by means of an automated cutting system.
- 3. Integrity: Execute messages in such a manner that edges and corners of finished letter forms are true and clean. Letter forms with round positive or negative corners, non-uniform stroke widths, nicks, cuts, or ragged edges will not be acceptable.

#### I Fabrication Individual Letters, Numbers And Logos

- 1. Pin-mounted Aluminum Welded Construction: Alloy 5005 H14, 3.125 [2.25] mm [(0.125 [0.090] inch)] thickness minimum unless noted otherwise.
- 2. Mounting distance from wall surface: As shown.
- 3. Depth of returns: As shown.

#### J Paints, Coatings, & Finishes

- 1. Paint Color References: Color references are for color designation only. Refer to Schedule at end of Section for applicable coating systems. Colors which may be indicated on Drawings include:
  - a. PMS: Pantone Matching System.
  - b. MAP (Matthews Acrylic Polyurethane): Matthews Paint Company.
  - c. HC: Benjamin Moore Historic colors.
  - d. BM: Benjamin Moore.
  - e. Lacryl: Spraylat Corporation.
- 2. Paint Formulation: Formulate paint materials with antimildew agents and carefully balance ultraviolet inhibitors for exterior materials.
- 3. Application:
  - a. Properly prepare subsurfaces and apply materials in sanitary environment.
  - b. Apply materials by method (brush, roller, spray) best suited to obtain required finish matching approved samples.
  - c. Ensure finish surfaces are free of brush marks, streaks, laps, runs, or pileup of paints, with uniform coverage.
- 4. Unless indicated otherwise, provide a satin finish.

# Boston Properties

The Link

	Р	V	Р	۲	a	n	Р	/
_	_	V	_		Ч	ч	~	7

Leverage Design Group, Inc. © 2019

No portion of this drawing may be reproduced without written consent of Leverage Design Group, Inc. The design elements represented on this sheet and related sheets are for design intent only.

Leverage Design Group, Inc. does not represent that the design of the elements on the sheets are able to be fabricated entirely as shown. Contractor/flabricator to review documents for contractibility, performance and structural soundness and to notify Leverage Design Group, Inc. in the event of concern or disagreement with the contractibility and design intent of the elements as depicted on the sheets.

REV#	DESCRIPTION	BY	DATE
<u> </u>			
<u> 2</u> _			
<u> 3</u> _			
<u> </u>			
<u></u>			
<u>6</u> _			
<u> </u>			

# Performance Specifications